

Self-Contained Hydraulic Cutters

▼ Shown from left to right: **WMC-2000, WMC-750**



- Rotating heads for operator convenience
- Guillotine action for easy operation
- Carrying bag included for easy carrying and tool protection
- Velcro straps to secure handles on larger models for easy carry
- Spring return for easy operation
- Light weight self-contained tool, can be used anywhere.

WMC Series



Capacity:

3 - 20 ton

Cutting Capacity:

14 - 85 mm

Maximum Operating Pressure:

700 bar



Replacement Blades

60-62HRC hardened replacement blades.

For Cutter Model Number	Order Blades Model Number
WMC-580	WCB-580
WMC-750	WCB-750
WMC-1000	WCB-1000
WMC-1250	WCB-1250
WMC-1580	WCB-1580
WMC-2000	WCB-2000
WMC-3380	WCB-3380



CAUTION !: A "☆" in the charts on these pages means that this hydraulic cutter is not designed to cut this size or type of material. Any attempt to do so may result in personal injury and damage to the unit and will void the warranty.

▼ Selection Chart Maximum Cutting Capacities (ø in mm)

Capacity ton	Model Number	Length (mm)	Steel Wire Rope, Hemp-core or IWRC 6x7 6x12 6x19	Round Bar				Wire Strand					Cable		Weight (kg)
				Copper Wire or Bar	Aluminum Wire or Bar	Soft Steel Bolts	Reinforcing Bar	Bare Copper Wire Strands	Bare Aluminum Wire Strands 6x7	ACSR Wire Strands	Guy Steel Wire Strands 1x7	Guy Steel Wire Strands 1x19	Telephone Cable CPP	Underground Cable (Power)	
4	WMC-580	381	16	16	16	16	☆	16	16	16	14	14	☆	16	3,6
4	WMC-750	381	19	17	17	17	☆	19	19	19	14	14	☆	17	3,6
20	WMC-1000*	679	☆	19	19	19	19	☆	☆	☆	☆	☆	☆	☆	11,3
20	WMC-1250	679	31	28	31	31	22	31	31	31	22	25	☆	☆	10,4
6	WMC-1580	558	19	19	19	19	☆	38	41	41	16	16	☆	41	6,8
13	WMC-2000	628	25	31	31	22	☆	50	50	50	19	19	☆	50	10,9
3	WMC-3380	660	☆	☆	☆	☆	☆	46	42	☆	☆	☆	85	85	10,0

* Cuts 12 mm alloy chain grade 70 (type G7 transport or tie-down) or grade 80 (for overhead lifting applications)

☆ Will not cut designated material